

MT-Profil R



UNIMES



For continuous level measurement in tanks containing fuel oil EL, diesel fuel, biodiesel and water.
For tanks heights from 0 to 250 cm.
Suitable for use in flood hazard areas.

Universal, mechanical level indicator with plastic planetary gear.
Measuring range is adjustable from 0 to 250 cm by reversible scale.

With reversible scale 0–150 cm and 0–250 cm for fast adaptation to the tank height. Odour-tight.

Watertight up to 10 m water column.

Measuring range (tank height) 0/150 to 0/250 cm

Displayed values 0/150 or 0/250 liquid level in cm

Connection thread G1 ½ or G2

Housing/float
Display: ABS, impact-resistant
Float: PE-HD

For continuous level measurement in tanks containing fuel oil EL, diesel fuel, biodiesel and other low-viscosity media which do not attack materials of the indicator.
For tank heights from 900 to 2,000 mm.

Universal mechanical level indicator with fully adjustable brass and nickel silver movement.
The pointer deflection amounts to 280° at tank heights and diameters from at least 900 mm to 2,000 mm maximum.
Indication in percentage of liquid level, litre scale can be retrofitted.
With reference pointer for consumption monitoring.

Measuring range (tank height) 0/900 to 0/2,000 mm

Displayed values 0/100 % liquid level

Connection thread G1 ½ and G2
Housing/float
Display: ABS, impact-resistant
Window: SAN
Float: PE-HD

Additional litre scales
For use with Unimes for all standard, cylindrical horizontal tanks.
When ordering, please specify the shape and capacity of tank.

Special scales
For Unimes and tanks of any shape and dimension.
When ordering, please include tank drawing or bearing chart.